



Triebwerksgruppe FEM classification Groupe FEM	1Bm	1Am	2m	3m	4m	Hub- geschw.	Leistung	Gewicht ausger.	Ketten- grösse	Ketten- gewicht		- Schutzart nach DIN 40050: - Isolierstoffklasse - Anschlussicherung generell - Lasthaken DIN 15401	IP55 F 16A	Rundstahlkette, Special chain, Chaîne spéciale:  Güteklasse, Grade, Classe qualité: DAT (8SS) nach, according to, selon: FEM 9.671
	150	180	240	300	360									
ED% Duty factor % Facteur de marche %	25%	30%	40%	50%	60%	Vitesse de levage	Puissance							
	kg	kg	kg	kg	kg	m/min.	kW (1Bm)	A (1Bm)	kg	mm	kg/m			
GCH 1600/2N	3200	2500	2000	1600	1250	4	2.44	6.0	73	9x27	1.75			
GCH 1600/2NF	3200	2500	2000	1600	1250	4/1	2.44/0.61	6.6/4.2	75	9x27	1.75			
GCH 1600/2SF	2000	1600	1250	1000	800	6.25/1.5	2.4/0.58	6.6/4.2	75	9x27	1.75			

**GCH 1600/2**

Massbild; Schematic draw.; Liste de dim.



94.08.9205.5

Massstab Echelle	Gezeichnet Dessiné	18.08.09	P.ENGEL
1:3	Gezeichnet Dessiné	22.10.10	S.NIEDERH.
	Geprüft Contrôlé	06.11.09	P.ENGEL
	Freigegeben Autorisé		

Index  
D